



تعيين	(الأبعاد الرئيسية (مم)					تقييمات الحمل الأساسية (KN)		سرعة محدودة (دورة في الدقيقة)		وزن
	د:	د:	ب:	روبية دقيقة	rs1min	ديناميكي ((كر	ثابت ((كو	شحم	بترول	(كلغ)
N2208	40	80	23	1.1	1.1	58	62	8500	10000	0.48
N2209	45	85	23	1.1	1.1	61.5	68	7600	9000	0.52
N2210	50	90	23	1.1	1.1	64	73.5	6900	8100	0.56
N2211	55	100	25	1.5	1.1	75.5	87	6300	7400	0.758
N2212	60	110	28	1.5	1.5	96	116	5800	6800	1.04
N2213	65	120	31	1.5	1.5	120	149	5400	6300	1.37
N2214	70	125	31	1.5	1.5	119	151	5000	5900	1.44
N2215	75	130	31	1.5	1.5	130	162	4700	5500	1.52
N2216	80	140	33	2	2	147	186	4400	5100	1.89
N2217	85	150	36	2	2	170	218	4100	4800	2.39
N2218	90	160	40	2	2	197	248	3900	4600	3.04
N2219	95	170	43	2.1	2.1	230	298	3600	4300	3.71
N2220	100	180	46	2.1	2.1	258	340	3500	4100	4.48
N2222	110	200	53	2.1	2.1	320	415	3100	3700	6.43
N2224	120	215	58	2.1	2.1	350	460	2900	3400	8.03
N2226	130	230	64	3	3	380	530	2600	3100	10
N2228	140	250	68	3	3	445	635	2400	2800	12.6
N2230	150	270	73	3	3	500	710	2200	2600	16