


VISTA®

Bearing



تعيين	(الأبعاد الرئيسية (مم)					تقييمات الحمل الأساسية (KN)		سرعة محدودة (دورة في الدقيقة)		وزن
	د:	د:	ب:	روبية دقيقة	rs1min	ديناميكي ((كر	ثابت ((كو	شحم	بترول	(كلغ)
NUP1006	30	55	13	1	0.6	19.7	19.6	14000	16000	0.13
NUP1007	35	62	14	1	0.6	22.6	23.2	12000	15000	0.179
NUP1005	25	47	12	0.6	0.3	15.1	14.1	16000	19000	0.092
NUP1008	40	68	15	1	0.6	27.3	29	11000	13000	0.22
NUP1009	45	75	16	1	0.6	31	34	9900	12000	0.28
NUP1010	50	80	16	1	0.6	32	36	8900	11000	0.295
NUP1011	55	90	18	1.1	1	37.5	44	8200	9700	0.442
NUP1012	60	95	18	1.1	1	40	48.5	7500	8800	0.474
NUP1013	65	100	18	1.1	1	41	51	7000	8200	0.485
NUP1014	70	110	20	1.1	1	58.5	70.5	6500	7600	0.699
NUP1015	75	115	20	1.1	1	60	74.5	6100	7100	0.738
NUP1016	80	125	22	1.1	1	72.5	90.5	5700	6700	0.98
NUP1017	85	130	22	1.1	1	74.5	95.5	5400	6300	1.03
NUP1018	90	140	24	1.5	1.1	88	114	5100	5900	1.33
NUP1019	95	145	24	1.5	1.1	90.5	120	4800	5600	1.4
NUP1020	100	150	24	1.5	1.1	93	126	4600	5400	1.45
NUP1021	105	160	26	2	1.1	105	142	4300	5100	1.84
NUP1022	110	170	28	2	1.1	131	174	4100	4800	2.33
NUP1024	120	180	28	2	1.1	139	191	3800	4400	2.44

NUP1000 Series

NUP1026	130	200	33	2	1.1	172	238	3400	4000	3.69
NUP1028	140	210	33	2	1.1	176	250	3200	3800	4.05
NUP1030	150	225	35	2.1	1.5	202	294	3000	3500	4.77